



MOUNTING SUGGESTIONS:

Victory Octane 2017 One-piece Seat

Hardware:	10mm x 16mm shoulder screw 8mm x 15mm buttonhead Allen screw
Tools needed:	5mm Allen wrench 6mm Allen wrench

Removal of Stock Seat:

1. Locate and remove the seat retaining bolt at the front of the seat using a 6mm Allen wrench.



2. Push the seat slightly forward, taking care not to hit the fuel tank, until the seat's rear bracket is clear of the fender mount.

3. Lift the back of the seat slightly, and pull the seat back and up to remove.

Installation of Mustang Seat:

1. Install the supplied 10mm x 16mm shoulder screw into the hole behind the tank. Tighten securely with a 6mm Allen wrench.

Note: The rubber filler panel can be removed if desired. It is not required for mounting the Mustang seat.



2. Remove the plug from the fender, revealing an 8mm threaded hole.



3. Engage the Mustang seat's front bracket with the shoulder screw and lower the seat to the fender.



4. Secure seat to fender using supplied 8mm x 15mm buttonhead Allen screw. Tighten securely with a 5mm Allen wrench.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75971, 79516

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.

