



Fitting Instructions for RAD0099BK/TI **Radiator Guard BLACK - Triumph Speed Triple '10-'15**

In This Kit There Should Be

- 1x Radiator Guard
- 2x 100mm Lengths of Foam
- 1 x Cable/Zip Ties



- To fit the radiator guard to the bike cut the foam strips provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator. Remove the original mounting bolt located at the top of the radiator on the right hand side as you look at the radiator from the front, (removing radiator/indicator side panels may aid this process) and also remove the two mounting bolts located at the bottom of the radiator. Fit the radiator guard into position and fix in place using the original mounting bolts previously removed and the cable/zip tie to secure the top left corner (as you look at the radiator).

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Instructions de montage pour RAD0099BK/TI **Protection radiateur noir - Triumph Speed Triple '10-'15**

Ce kit doit contenir :

- 1x Protection radiateur
- 2x 100mm bandeaux de mousse
 - 1 x serre câble



- Couper la mousse en bandeaux de 10mm de large et collez les au bas du cadre de la protection radiateur, de façon à ce que ces mousses soient situées entre la protection radiateur et le radiateur.
- Enlever le boulon d'origine placer sur le haut du radiateur du coté droit lorsque vous regarder le radiateur par devant (enlever les panneaux de clignotants/radiateurs devrait faciliter cette étape) et enlever également les 2 boulons de fixation placés au bas du radiateur.
- Fixer la protection radiateur en position en utilisant les boulons de fixation d'origine retires précédemment et les serre câble pour fixer le coté gauche en haut (lorsque vous regardez le radiateur).

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Montageanleitung für den RAD0099BK/TI **Kühlerschutz SCHWARZ - Triumph Speed Triple '10-'15**

Dieser Kit enthält:

- 1x Kühlerschutz (RAD0096)
- 2x 100mm Schaumstoffstreifen
 - 1x Kabelbinder



- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoffstreifen in 10 mm breiten Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind. Entfernen Sie die Originalschraube oben rechts (von vorne gesehen) am Kühler (die Entfernung der Kühler/Blinker-Seitenverkleidung vereinfacht diesen Schritt) und entfernen Sie die zwei Montageschrauben unten am Kühler. Den Kühlerschutz mit den Originalschrauben in Position fixieren und mit dem Kabelbinder oben links in der Ecke (von vorne gesehen) befestigen.