

## DUCATI SLIPPER CLUTCH SCRAMBLER 695 696 796 + SPRINGS

20003 Antihopping slipper clutch Ducati Hypermotard/Monster 796+696

– mounting instructions

Congratulations, you bought one of best clutch systems for your Ducati .

This clutch should be installed by an experienced Ducati workshop, or mechanic.

1. Read these instructions with photos before you start. Check if the set includes all parts according to list.
2. Remove standard clutch drum according to Ducati workshop manual, clean the thread on the shaft and big nut from old glue with brake cleaner.
3. Check positioning of standard shim between basket and drum (pic.a).
4. Install pre mounted slipper drum. ( pic. b )
5. Put steel (kit) washer ( pic. c ) and the OEM main nut . Fix the nut with torque 180 Nm and safe it with glue Loctite No.620 (RED) (pic. d, e,).
6. This clutch is designed for using STD clutch plates and springs delivered for Ducati 1098/1198 ( pic.j ). All clutch plates put as standard. (pic. f ).In case of using new friction plates, it is highly recommended to let these plates soak in engine oil for 24 hours.
7. Remove standard push rod (pic. g) from STD pressure plate, and press it into kit pressure plate (pic. h).
8. Install pressure plate ( pic.i )
9. Install clutch springs (Ducati 1098/1198 )( pic.j,k ) , put spring retainers ( kit ), and fix all with bolts ( kit ) – torque 10 Nm ( pic. l,m, ).
10. Install the case cover according to Ducati workshop manual, always use new cover gasket

### PARTS LIST

- 1 pc. Pre mounted slipper drum
- 1 pc. Pressure plate
- 4 pcs. Clutch spring
- 4 pcs. Spring retainer
- 4 pcs. Bolt
- 1 pc. Big washer
- 4 pcs. + preload springs retainers