

Denali Horn Mount

Kawasaki Concours GTR1400
'08-'15

HMT.08.10000 Instructions Rev:00

PLEASE READ BEFORE INSTALLING

TWISTED THROTTLE products should be installed by a qualified, experienced motorcycle technician. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. TWISTED THROTTLE takes no responsibility for damages caused by improper installation.

All screws, bolts, and nuts, including all replacement hardware provided by TWISTED THROTTLE should be tightened to the torque specified in the OEM maintenance manual for your motorcycle. If no torque specifications are provided in the OEM maintenance manual, the following torques may be used:

| | |
|---------|-------------------|
| M5..... | 3.5 ft-lbs (5 Nm) |
| M6..... | 7 ft-lbs (9.6 Nm) |
| M8..... | 13 ft-lbs (18 Nm) |

All screws, bolts, and nuts should be checked after driving the first 30 miles (50 km) to ensure that all are tightened to the proper torque.

Medium strength liquid thread-locker (i.e., "Loctite") should be used to secure all screws, bolts, and nuts.

Distributed by:

| | |
|---|---|
| Twisted Throttle LLC 570 Nooseneck Hill Rd Exeter, RI 02822 | phone: 855.255.5550 fax: 401.223.6955 www.twistedthrottle.com |
|---|---|



Installation Instructions



Step One: Remove the right hand side fairing to expose the mounting point illustrated below. Using the hardware that is supplied with the horn bolt the horn the mounting bracket (#1). Next used the supplied M6 bolt (#2) to bolt bracket (#1) to the mounting point illustrated below.

