



# Installation Instructions for Mustang One-Piece Seat on 2007-2011 Yamaha V-Star 1300 and V-Star 1300 T

## Removal of stock seat

1. Insert ignition key into left side cover and turn counter-clockwise to release front seat from latch.



2. Lift nose of seat, then remove front seat from frame.



3. Remove two mounting bolts from under front of rear seat.



4. After bolts have been removed, lift front of rear seat up and pull seat forward to release it from the rear fender bracket.



5. Remove rear seat mounting bracket from fender as it is not needed for installation of Mustang one-piece seat.



# Installation Instructions for Mustang One-Piece Seat on 2007-2011 Yamaha V-Star 1300 and V-Star 1300 T

## Installation of Mustang seat

1. Turn seat over and note locations of rear bracket and front latch bracket on baseplate of seat.



2. Tilt seat upward and push it back to engage the rear seat bracket into the rear fender bracket on the bike.  
(Center bracket on fender has been removed earlier)



3. Align front latch bracket on seat with latch mechanism on frame and push front of seat down firmly to engage latch.



4. Completed installation should look like picture shown here.

These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".