



# Mounting Suggestions

## Yamaha V-Star 950 2009-2011

### Two-Piece Seat



#### Baseplate Features:

The two-piece, marine grade fiberglass baseplate mounts like the stock seat. Rubber bumpers protect the frame and fender.

#### Removal of Stock Two-Piece Seat:

1. Insert ignition key into the right side cover and turn counterclockwise until a click is heard. Solo seat is now unlocked.
2. Lift up on the nose of solo and remove the seat from the frame.



3. The stock rear seat's two mounting bolts are now accessible. Use a 10mm socket with extension to reach bolts and then remove.
4. With bolts removed, slide rear seat forward and off of the bike.



## Mounting of Mustang Seat:

The Mustang seat installs just like the factory seat.

1. Slide the rear seat back into the fender's U-Bracket.
2. Install the original two 8mm mounting bolts through the rear seat's brackets and into the fender bracket. Tighten the bolts with a 10mm socket.



3. Slide our solo seat's rear tongue bracket into the fender receiver. Align our front bracket with the frame's latch.
4. Push the front of the seat down to lock.



Thank you for choosing Mustang and enjoy your ride.



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to [questions@mustangseats.com](mailto:questions@mustangseats.com), or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Ref part #76070, 76071, 79570, 79571